

Model	RSC-1650H	RSC-1650C	RSC-1400C
Power Supply	AC100~120V / 220~240V / 50~60Hz		
Power Consumption	1650 W	150 W	100W
Max. Laminating Width	65 " / 1650 mm		55" / 1400 mm
Laminating Thickness	1~10 mil / 25~250 mic		
Laminating Speed	16.4 ft/min / 5 m/min		
Read Time	10 min	0 min	
Heating Method	Hot Roller	None	
Driving Motor	DC geared motor		
Temperature Control	Digital(micom) up to 122°F	None	
Speed Control	Digital(micom) 9 settings		
Transport Type	2 Roller		
Cross Cutter	Yes		
Cold Lamination	Yes		
Mount / Foam Board	Yes (15 mm)		
Reverse	Yes		
Remote Control	Yes		
Foot pedal	Yes		
Unit Dimensionss (W x D x H)	77.2 x 25.6 x 47.4 (inch) 1960 x 650 x 1210 (mm)	77.2 x 25.6 x 47.4 (inch) 1960 x 650 x 1210 (mm)	67.5 x 25.6 x 47.4 (inch) 1710 x 650 x 1210 (mm)
Unit Weight	550 lbs / 250Kg	550 lbs / 250Kg	361bs / 164Kg
Carton Dimensions (W x D x H)	84.5 x 34.9 x 51.8 (inch) 2150 x 888 x 1318 (mm)	84.50 x 34.9 x 51.8 (inch) 2150 x 888 x 1318 (mm)	76.5 x 34.9 x 33.5 (inch) 1960 x 888 x 1318 (mm)
Carton Weight	704 lbs / 320 Kg	704 lbs / 320 Kg	6151bs / 279Kg